

Australian Wool Testing Authority Ltd - trading as AWTA Product Testing A.B.N 43 006 014 106

1st Floor, 191 Racecourse Road, Flemington, Victoria 3031 P.O Box 240, North Melbourne, Victoria 3051 Phone (03) 9371 2400

Client :	Aventing Cr	oup Pty I to T/AS Mondany	ood Floors		Test	Number :	21-0030	47
	Aventino Group Pty Ltd T/AS Wonderwood Floors Unit 1/27 Leeds Street					e Date :	1/07/202	
	Rhodes NS					Date :	5/07/202	
Sample D	escription	Clients Ref : "14mm Engineered Timber Flooring"						
		Engineered timber flooring planks						
		Colour : Oak						
		End Use : Flooring Nominal Composition : Solid oak veneers adhered to multilayer plywood						
		Nominal Composition :			•	er plywood		
		Nominal Mass per Unit A Nominal Thickness :	rea/Density : 14mm	650kg/r	m3			
			1411111					
6 4586-2013	;	Slip Resistance Classifi	cation of new	Pedestrian	Surface Mate	erials		
ppendix A								
pendix A		Wet Pendulum Test Met	hod					
pendix A		Wet Pendulum Test Met Date of Testing	hod				30/06/2021	1
opendix A							30/06/2021	
opendix A		Date of Testing	legC)	ed with pH neutr	al detergent and	d dried.		
ppendix A		Date of Testing Test Temperature (20±5c	legC)		al detergent and	d dried.		
ppendix A		Date of Testing Test Temperature (20±5c Sample Preparation	legC) Washe		ral detergent and	d dried.		2 °C
pendix A		Date of Testing Test Temperature (20±5c Sample Preparation Test Direction	legC) Washe		al detergent and	d dried.	22	2 °C
pendix A		Date of Testing Test Temperature (20±5c Sample Preparation Test Direction Fixed/Unfixed	legC) Washe		ral detergent and	d dried. 4	22 Unfixed	2 °C d
pendix A		Date of Testing Test Temperature (20±5c Sample Preparation Test Direction Fixed/Unfixed Slider No 96 Batch No Length British Pendulum	legC) Washe Length				22 Unfixed 95	2 °C d 5 SRV
pendix A		Date of Testing Test Temperature (20±5c Sample Preparation Test Direction Fixed/Unfixed Slider No 96 Batch No Length	legC) Washe Length	2	3	4	22 Unfixed 98 5	2 °C

Equipment: Cooper Pendulum Skid Tester Serial No: 1433-01 Calibrated 08/11/2019 Slider prepared using P400 and 3µm lapping film.

These results apply only to the specimens tested and it is recommended that before selection of flooring or paving materials the effect of service conditions, including maintenance and wear on their slip resistance be checked.

241586

52369

C Australian Wool Testing Authority Ltd Copyright - All Rights Reserved



Accredited for compliance with ISO/IEC 17025 - Testing

Samples and their identifying descriptions have been provided by the client unless otherwise stated. AWTA Ltd makes no warranty, implied or otherwise, as to the source of the tested samples. The above test results relate only to the sample or samples tested. This document shall not be reproduced except in full and shall be rendered void if amended or altered. This document, the names AWTA Product Testing and AWTA Ltd may be used in advertising providing the content and format of the advertisement have been approved by the Managing Director of AWTA Ltd.

12



MICHAEL A. JACKSON B.Sc.(Hons)

Page 1 of 1



Fiona McDonald