WONDERWOOD LAMINATE FLOORING

INSPIRED BY NATURE. CRAFTED WITH PASSION.

Collection 2017/2018



LUXE LAMINATE RANGE



New Hydromate Flooring

More water resistant than ever

Your flooring needs to stand up to the wear and tear of everyday life. The new Hydromate range has been created with a tighter clicking system and a protective aluminium oxide layer. This clever design prevents liquid from finding its way under the surface of your floor.

Choose Hydromate for:

- A stunning visual finish
 - Superior quality
- 48 hour water resistance
- Reduced risk of swelling and distortion

Other floorboards are instantly susceptible to damage from water and other liquids. While Hydromate is not 100% waterproof, it provides better protection against everyday liquid spills than any other product.



BRAVADO WL-60221

LAVA GREY WL-60223

TRENDY WL-60225



BROWN OAK

WL-60233

NEM





DAPPLE GREY WL-60229

WHITE OAK WL-60231

PLANK SIZE 2250 x 238 x 12mm



FRENCH OAK WL-60232

SPECIFICATION

Surface Finish	Matt Finish with EIR Technology
Edging	4 Sided Micro-Bevel
Joining System	Uniclic Patented Technology
Abrasion Resistance	Certified AC4
Formaldehyde Emission	<e1< th=""></e1<>
Fire Test/ CHF Value	6.1 Kw/M2
Fire Test/ Smoke Value	4%.min
Slip Resistance	P2
AS 4266.8:2004 - 24hr Thickness Swell: Maximum 9%	0.10%
Pack Size	4 Panels/ 2.142 m2/ Carton

PREMIUM LAMINATE RANGE



Available in a wide variety of shades, each panel features an embossed wood grain texture, offering a realistic effect. Our premium laminate range is ideal for homes and offices and is created to withstand regular foot traffic.



COUNTRY OAK T21963

SNOWY OAK T21965

URBAN PEARL T21971

BIANCO T21975

GREY CANVAS T21977

NEM



T21979





MILTON GREY

T21987

SPOTTED GUM

T21988

PELACO T21989



T21986

SPECIFICATION

Surface Finish	Matt Finish with EIR Technology
Edging	4 Sided Micro-Bevel
Joining System	Valinge
Abrasion Resistance	Certified AC4
Formaldehyde Emission	<e1< td=""></e1<>
Fire Test/ CHF Value	8.2Kw/M2
Fire Test/ Smoke Value	2%.min
Slip Resistance	P2
AS 4266.8:2004 - 24hr Thickness Swell: Maximum 9%	0.00%
Pack Size	5 Panels/ 2.156 m2/ Carton



PALOMA T21990

WINTERIDGE T21992

To view our full testing report please visit aventinogroup.com

FINISHING PROFILES



STAIR NOSING 2400 x 72 x 24mm Stair finishing should not be used for commercial applications



LUXE STAIR NOSING 2400 x 115 x 24mm


Stair finishing should not be used for commercial applications




SCOTIA 2400 x 28 x 15mm



T - MOULDING 2400 x 28 x 15mm



CARPET REDUCER 2400 x 35 x 15mm



REDUCER 2400 x 45 x 15mm

LAMINATE COMPOSITION

ALUMINIUM OXIDE WEAR LAYER

Abrasion resistance rated AC4

DECORATIVE LAYER

HDF CORE

with patented clicking system

BACKING BALANCING LAYER

Ensures structural stability

WARRANTIES



WONDERWOOD

estic Warra

Välinge

UNICLIC Patented Tech

www.wonderwoodfloors.com.au





100

TERMS & CONDITIONS:Colour and grain of product image in this brochure may differ from the actual product due to colour variation in the printing process.All product purchases are subject to Wonderwood Floors standard terms & conditions of sale. Please refer to our installation guideline, maintenance and warranty document for further clari⊠cation. Our products come with guarantees that cannot be excluded under the Australian Consumer Law. Consumers are entitled to a replacement or refund for a major failure and compensation for any other reasonably foreseeable loss or damage. Consumers are also entitled to have the goods repaired or replaced if good fail to be of acceptable quality and the failure does not amount to a major failure. Please refer to our warranties on www.aventinogroup.com